

Protocollo d'impresa in servizio MAN

Viaggio di messa in servizio del: 17.05.09



Regime raccomandato	giri/min	900	1200	1400	1600	1800	1950	2150	Nominale	Max.
Temp. acqua mare a valle mot. sx	°C	83.4	84.4	84.4	85.0	85.6	86.4	87.2	88.2	89.1
Temp. acqua mare a valle mot. centr.	°C									
Temp. acqua mare a valle mot. dx	°C	85.0	85.1	85.9	86.0	86.6	87.1	88.0	88.6	89.9
Cons. carb. sx	l/h	12.3	23.1	34.1	48.0	65.1	84.9	112.0	122.9	127.1
Cons. carb. centr.	l/h									
Cons. carb. dx	l/h	12.4	23.4	34.0	48.5	65.3	85.1	112.4	123.0	127.2
Tens. batt. sx	Volt	25.7	25.7	25.7	25.7	25.6	25.6	25.6	25.5	25.5
Tens. batt. centr.	Volt									
Tens. batt. dx	Volt	25.7	25.7	25.7	25.7	25.7	25.7	25.6	25.6	25.6
Carico relativo sx	%	32.1	31.4	40.6	49.2	57.9	65.9	84.4	94.5	99.0
Carico relativo centr.	%									
Carico relativo dx	%	34.0	31.2	40.8	50.0	58.4	66.0	85.6	95.1	100.0
Carico/coppia sx	mq/hub	66.9	91.0	115.0	137.4	169.2	196.9	234.6	253.0	263.0
Carico/coppia centr.	mq/hub									
Carico/coppia dx	mq/hub	70.1	89.0	115.1	140.3	171.3	2.3.6	244.9	262.1	266.0
Leva di marcia sx	%	19.0	37.0	47.0	59.0	70.0	81.0	88.0	90.0	100.0
Leva di marcia centr.	%									
Leva di marcia dx	%	20.0	37.0	48.0	59.0	70.0	81.0	88.0	90.0	100.0
Flusso acqua di mare sx	l/min	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Flusso acqua mare centr.	l/min									
Flusso acqua di mare dx	l/min	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0